



250kVA Soundproof Generator



Features

- Noise Level @ 1m, 75dBA (@7m, 63dBA)
- Autostart DSE CP with MCCB
- VELCB
- Micro Switch Protection over Buss Bar Door
- Oil Extraction Pump
- 3 Way Fuel Valve
- Battery Isolator
- Water Separator Std
- Cental Lifting Hook
- Fork Lift Pockets
- Fully Bunded
- Battery Charger



Options

- Bulk Fuel Tank

| Generating Set | 50 Hz | 60 Hz |
|---------------------------|-----------------------|---------------------|
| Continuous Power | 250 kVA | 289 kVA |
| Standby Power | 275 kVA | 318 kVA |
| Noise Level @ 1m / 7m | 75 dBA / 63 dBA | |
| Power Factor | cos ϕ 0.8 | |
| Continuous Power | 200 kW _e | 240 kW _e |
| Standby Power | 220 kW _e | 265 kW _e |
| Amps 3 Phase | 347 A | |
| Fuel consumption 70% load | 46 l/h | 54 l/h |
| Engine | 1500 rpm | |
| Model | Cummins QSL9G3 | |
| Continuous Power | 217 kW _m | |
| Standby Power | 239 kW _m | |
| Aspiration | Turbocharged | |
| Cooling System | Water | |
| Speed Governor | Electronic | |
| Cylinder Number | 6 | |
| Displacement | 8,700 cm ³ | |
| Logistic Information | GQ275C | |
| Fuel Tank | 450 ltr | |
| Weight (Wet) | 3,900 kg | |
| Dimensions (L x W x H) | 380 x 120 x 230 cm | |
| Control Panel | Deep Sea 7510 | |
| Auto Start | Standard | |

Deep Sea 7510 Loadshare Control Panel



ABIRD has a policy of continuous improvement and therefore reserve the right to change the specification without prior notice.