NEVER allow yourself or others to be in a position between the load and a wall or other fixed structures as you could become trapped and seriously injured.

Take your time and don't overdo it. You are more likely to have an accident if you are tired or rushing.

FOUIPMENT CARE

Never push the equipment beyond its design limits. If it will not do what you want with reasonable ease and speed, assume you have the wrong equipment for the job. Contact your local HSS Lift & Shift Depot for advice.

Keep the equipment clean, you will find this less of a chore if you clean it regularly, rather than wait until the end of the hire period.

When not in use, store the equipment somewhere clean, dry and safe from thieves and unauthorised users.

FINISHING OFF

Remove the crowbar from the load, then give the equipment a final clean up ready for return, to your local HSS Lift & Shift Depot.



...any comments?

If you have any suggestions to enable us to improve the information within this guide please fax your comments or write to the Product Manager at the address below

Fax: 0181-687 5001


©HSS Hire Service Group Plc 1999 No. LS47/01

Group Office: 25 Willow Lane, Mitcham, Surrey CR4 4TS

Web Site: http://www.hss-liftandshift.co.uk

Operating & Safety Guide LS47

HSS Lift & Shift



Pinch & Roller Crowbars

A simple tool for lifting and manoeuvring small machines or office furniture.





Code 70510/70520

GENERAL SAFETY

For advice on the safety and suitability of this equipment contact your local HSS Lift & Shift Depot.

There is a serious risk of personal injury if you do not follow all instructions laid down in this guide.

This equipment is designed to be used by an able bodied, competent adult who has read and understood these instructions. Anyone with either a temporary or permanent disability should seek expert advice before using it.

Keep children, animals and bystanders away from the work area. Cordon off a NO GO area using cones and either barriers or tape, available for hire from your local HSS Lift & Shift Depot.



Never use this equipment if you are ill. feeling tired, or under the influence of alcohol or drugs.



Wear practical, protective clothing, gloves and footwear. Avoid loose garments

and jewellery that could catch in moving parts, tie back long hair.

Safety Warning

This equipment MUST NOT be used to carry or lift personnel.

Make sure you know how to operate this equipment safely and are aware of its limitations before you use it.

It is both the hirer's and the operator's responsibility to perform a risk assessment before using this **equipment.** You are also responsible for the safety of any person in the work area.

Make sure that anyone in the immediate work area is warned of what you are doing.

Be aware of the raised load when close to ceilings or other overhead obstructions.

Comm Code	SWL
70510	1,000kg
70520	1,500kg

exceed the equipment's safe working load, see chart.

Check the condition of the equipment before

use. If it shows signs of damage or excessive wear, return it to your local HSS Lift & Shift Depot.

GETTING STARTED

This equipment must only be used on a surface capable of withstanding the weight of the load.

Thoroughly clear and clean the floor area to remove oil, grease and swarf.

Ensure you have selected a set of pinch or roller crowbars that are designed for the item's weight.

Have to hand, any lifting and pulling equipment needed for the job. HSS can offer for hire, various components depending on what you are trying to achieve.

The equipment available ranges from nylon and wire ropes, shackles, manual and hydraulic tirfor winches, to machine moving skates and toe jacks. For advice on the range of equipment, contact your local HSS Lift & Shift Depot.

Check that the route to the destination is clear and the surface is suitable for both the weight and the pinch or roller crowbars.

Assess the load's design to determine the best position for the crowbar, the load must balance correctly on the crowbar's tongue.

The contact point of the load MUST be able to support its weight, i.e. a suitable jacking point, in the same way as jacking a car.

Determine the best position for the crowbar.


Under no circumstances must anyone allow their hands or feet under the load, when raised on the crowbar.

Next place the front tip of the crowbar's tongue under the front of the load.

The crowbar should be in a position whereby the load will be evenly distributed and safely balanced.

With the load raised on the crowbar's tongue, double check that everything is OK, make sure that the contact point between the load and crowbar is strong enough.

BASIC TECHNIQUES



The crowbar must not be steered with the load **stationary**, steering may only occur when the load is moving.

Attach suitable moving equipment to the load. Where the load allows, have helpers push from behind.

When the load is moving always position yourself so you can control the crowbar while staying clear of the raised load.

Continually check the path behind and in front of you to make sure there are no trip hazards.

Do not allow the load to travel at speed or change its direction of travel abruptly.